

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. **(Currently Amended)** A three wheel vehicle, comprising:
 - a frame having a front portion and a rear portion;
 - a pair of front wheels rotatably connected to the front portion of the frame;
 - a single rear wheel rotatably connected to the rear portion of the frame;
 - a straddle type vehicle seat connected to the frame;
 - a ~~structure defining a cavity therein~~ storage compartment disposed at the front portion of the frame between the pair of front wheels;
 - an engine connected to the frame, wherein the engine provides power to drive at least one of the single rear wheel and the pair of front wheels; and
 - a radiator system for cooling the engine, wherein the radiator system includes a first radiator.
2. **(Previously Presented)** A three wheel vehicle according to claim 1, wherein the first radiator is located on one side of the frame and a second radiator is located on an opposite side of the frame.
3. **(Currently Amended)** A three wheel vehicle according to claim [[1]] 2, wherein the second radiator is spaced apart from and is fluidly connected to the first radiator.
4. **(Currently Amended)** The three wheel vehicle according to claim [[1]] 2, wherein each of the first and second radiators ~~[[are]]~~ is located rearwardly of the pair of front wheels.
5. **(Currently Amended)** The three wheel vehicle according to claim [[1]] 2, wherein each of the first and second radiators is disposed at an angle with respect to a vertical axis of the vehicle.
6. **(Currently Amended)** The three wheel vehicle according to claim [[1]] 2, wherein each of the first and second radiators is disposed at an angle with respect to a longitudinal axis of the vehicle.

7. **(Currently Amended)** The three wheel vehicle according to claim [[1]] 2, wherein each of the first and second radiators is disposed substantially parallel to a longitudinal axis of the vehicle.
8. **(Currently Amended)** The three wheel vehicle according to claim [[1]] 2, wherein at least one of the first radiator and the second radiator includes a fan assembly for directing air through the at least one of the first radiator and the second radiator.
9. **(Previously Presented)** The three wheel vehicle according to claim 8, wherein each fan assembly is arranged to direct a flow of air towards a centerline of the vehicle, whereby the flow of air flushes hot air away from the engine.
10. **(Currently Amended)** The three wheel vehicle according to claim [[1]] 2, further comprising a fairing assembly enclosing at least the front portion of the frame, the fairing assembly including a first radiator enclosure for enclosing at least a portion of the first radiator and a second radiator enclosure for enclosing at least a portion of the second radiator.
11. **(Previously Presented)** The three wheel vehicle according to claim 10, wherein at least one of the first radiator enclosure and the second radiator enclosure includes a venting assembly for selectively venting air from at least one of the first and second radiator enclosures, the venting assembly being movable between an open position in which air from at least one of the first and second radiator enclosures is directed onto the rider and a closed position.
12. **(Canceled)**
13. **(Currently Amended)** The three wheel vehicle according to claim 2, wherein the ~~avity~~ storage compartment is positioned between the first radiator and the second radiator.
14. **(Currently Amended)** The tree wheel vehicle according to claim 1, wherein the ~~avity~~ storage compartment includes a cover to provide access to the ~~avity~~ storage compartment when the cover is at an open position.

15. **(Currently Amended)** The three wheel vehicle according to claim 1, further comprising a removable ~~storage compartment~~ insert located within the ~~cavity~~ storage compartment.

16. **(Currently Amended)** The three wheel vehicle according to claim 1, wherein the ~~cavity~~ storage compartment provides access to an engine service center.

17. **(Previously Presented)** A straddle type three wheel vehicle, comprising:
a tubular frame having a front portion and a rear portion, the tubular frame having a head pipeless construction;
a pair of front wheels rotatably connected to the front portion of the frame;
a single rear wheel rotatably connected to the rear portion of the frame, each of the pair of front wheels and the single rear wheel including a tire suitable for road use;
handlebars operatively rotatable connected to the frame and operatively connected to the front wheels to steer the vehicle;
a straddle vehicle seat connected to the frame, the seat being sized to accommodate at least two riders;
a storage compartment supported by the frame disposed between the pair of front wheels in front of the handlebar, the storage compartment having a cover;
an engine connected to the frame, the engine providing power to drive at least one of the single rear wheel and the pair of front wheels; and
a vehicle suspension system operatively connected to at least one of the pair of front wheels and the single rear wheel.

18. **(Currently Amended)** The three wheel vehicle according to claim 17, further comprising a radiator system for cooling the engine, the radiator system including a first radiator and a second radiator.

19. **(Original)** The three wheel vehicle according to claim 18, wherein the first radiator is located on one side of the frame and the second radiator is located on an opposite side of the frame.

20. **(Currently Amended)** The three wheel vehicle according to claim 17, wherein the tire ~~capable of~~ suitable for road use is a tire having a pressure of between 138 kPa [20 psi] and 345 kPa [50 psi].

21. **(Currently Amended)** The three wheel vehicle according to claim 1, wherein the structure defining the ~~cavity~~ storage compartment is a fairing assembly.